



**INTERNO** - INCASSI A MOLLE  
**INDOOR** - RECESSED WITH SPRINGS



Orientabile  
Adjustable



CRI > 90 3000K (W)  
Alto indice di resa cromatica  
High colour rendering index



2 STEP MACADAM 3000K  
Elevata precisione cromatica  
High chromatic precision



DGA COOLER MAX  
Sistema di dissipazione brevettato  
Patented heat dissipation system



180

## Stella 3 R



IP52



Class III



Incasso a parete, soffitto  
Wall, ceiling recessed



Cavo 60 cm con connettore rapido  
60 cm cable with quick connector



Collegare in serie 350mA o 500mA  
Connect in series at 350mA or 500mA



200 gr



Ø 64 mm





Controcassa per cemento e muratura  
Recessed Box for concrete and brickwork

page 564



ECO Energy Saving



**3W**  
350mA

Lumen 3000K

300lm

10° Lens 730326. \_ \_

30° Lens 760326. \_ \_

60° Lens 750326. \_ \_

**6W**  
500mA

Lumen 3000K

450lm

10° Lens 730553. \_ \_

30° Lens 760553. \_ \_

60° Lens 750553. \_ \_

**3W RGB**  
350mA

10° Lens 730326. \_ 7

30° Lens 760326. \_ 7

[www.dga.it/photometrics](http://www.dga.it/photometrics)

FINISHING

Alimentatori consigliati  
Suggested drivers

**350mA**  
CC20-F-350-N  
page 553

**500mA**  
CC20-F-500-N  
page 554

**350mA RGB**  
CC36-X-350-N  
page 560

FINISHING

3 Grigio - Gray  
4 Nero - Black  
7 Bianco - White

LED COLOUR

Y 2700K  
6 3000K  
W 3000K CRI > 90  
9 4000K  
1 5000K

